

# Containment Fill Station

## MEETS NFPA 1900 FOR AIR FILLING APPLICATIONS!

The next generation of American Airworks BoomBox™ 6000 PSI Class 2 containment air filling stations for SCBA and SCUBA is now available. Explosion-tested and certified by a third party, it meets the NFPA 1900:2024 edition standards.

The new BoomBox™ line of air filling stations include a newly designed gas assisted door operation to minimize operator fatigue.

Available for both mobile and stationary applications.

The BoomBox6K™ 3 Position Air Filling Station:

- Required on all new fire trucks per NFPA 1900.
- Recommended for fire stations and SCUBA shops.
- Single action locking bar activation.
- Includes 3 filling hoses with on/off controls & bleed valves.
- 2216/4500/5500 PSI stainless steel hand-tight nut and nipple, eliminates the need to switch between low and high-pressure fill adapters during the filling process.
- Bottom venting only enhances operator safety by reducing the risk of tip-over in the event of a cylinder rupture.
- Fills either 111 cu. ft. SCBA or 120 cu. ft. SCUBA cylinders up to 9.25 in. x 32.375 in.
- Available with 45° or 90° door opening configurations.
- Direct replacement option for older 4500 PSI limited fill stations.
- Custom air control panel configurations available upon request.

\*NFPA 1900:2024 consolidates the previous NFPA 1901 Standard for Automotive Fire Apparatus and related standards, effective January 1, 2024.



AC70530SP



AC70530RP



AC70530A-4A

EACH FILL STATION IS AVAILABLE WITHOUT THE STATIONARY MOUNTING BASE FOR MOBILE INSTALLATIONS

PART NUMBER	DESCRIPTION	DIMENSIONS (HxWxD)		WEIGHT	
		in	mm	lbs	kg
AC70530SP	Stationary, Standard Panel	52 x 40 x 21	(1321 x 1016 x 533)	960	435
AC70530SPM	Mobile, Standard Panel	46 x 40 x 21	(1168 x 1016 x 533)	848	385
AC70530RP	Stationary, Regulated Panel	52 x 40 x 21	(1321 x 1016 x 533)	963	437
AC70530RPM	Mobile, Regulated Panel	46 x 40 x 21	(1168 x 1016 x 533)	850	386
AC70530A-4A	Stationary, 4 Bank Panel	57 x 40 x 21	(1448 x 1016 x 533)	983	446
AC70530A-4AM	Mobile, 4 Bank Panel	51 x 40 x 21	(1295 x 1016 x 533)	870	395
AC70530A-4B	Stationary, 4 Bank Panel with Remote Fill	57 x 40 x 21	(1448 x 1016 x 533)	989	449
AC70530A-4BM	Mobile, 4 Bank Panel with Remote Fill	51 x 40 x 21	(1295 x 1016 x 533)	873	396
AC70530A-4C	Stationary, 4 Bank Panel with Priority Fill Selection	57 x 40 x 21	(1448 x 1016 x 533)	988	448
AC70530A-4CM	Mobile, 4 Bank Panel with Priority Fill Selection	51 x 40 x 21	(1295 x 1016 x 533)	872	396
AC70530A-4D	Stationary, 4 Bank Panel with Remote Fill & Priority Fill Selection	57 x 40 x 21	(1448 x 1016 x 533)	993	450
AC70530A-4DM	Mobile, 4 Bank Panel with Remote Fill & Priority Fill Selection	51 x 40 x 21	(1295 x 1016 x 533)	877	398


\*Adaptors for filling SCUBA cylinders may be purchased seperately.

PO Box 1000 | Sophia, WV 25921-1000  
 304-683-4595 | 304-683-3257 | 800-523-7222  
 sales@americanairworks.com | www.americanairworks.com



MORE  
INFO  
ONLINE





# Containment Fill Station

## MEETS NFPA 1900 FOR AIR FILLING APPLICATIONS!

The American Airworks BoomBox™ is designed for maximum operator protection. Engineered to contain the destructive force of an accidental cylinder failure or hose rupture, it safely redirects the air blast away from the user. Independently explosion-tested, third-party certified, and fully compliant with NFPA 1900:2024 edition standards, the BoomBox™ provides unmatched confidence and peace of mind with every fill.

Designed with the operator in mind, the new BoomBox™ filling stations feature an advanced gas-assisted door mechanism that minimizes fatigue and ensures effortless operation.

The BoomBox6K™ 3 Position Air Filling Station:

- Recommended for fire stations and SCUBA shops.
- Single action locking bar activation.
- Durable stainless steel, hinged air control panels for easy maintenance access.
- Includes 3 filling hoses with on/off controls & bleed valves.
- 2216/4500/5500 PSI stainless steel hand-tight nut and nipple, eliminates the need to switch between low and high-pressure fill adapters during the filling process.
- Bottom venting only enhances operator safety by reducing the risk of tip-over in the event of a cylinder rupture.
- Fills either 111 cu. ft. SCBA or 120 cu. ft. SCUBA cylinders up to 9.25 in. x 32.375 in.
- Direct replacement option for older 4500 PSI limited fill stations.
- Custom air control panel configurations available upon request.

\*NFPA 1900:2024 consolidates the previous NFPA 1901 Standard for Automotive Fire Apparatus and related standards, effective January 1, 2024.



AC70530T-4A



AC70530TB

PART NUMBER	DESCRIPTION	DIMENSIONS (HxWxD)		WEIGHT	
		in	mm	lbs	kg
AC70530T-4A	Stationary, Standard 4 Bank Panel	70 x 40 x 21	(1778 x 1016 x 533)	1054	478
AC70530T-4B	Stationary, 4 Bank Panel with Remote Fill	70 x 40 x 21	(1778 x 1016 x 533)	1057	479
AC70530T-4C	Stationary, 4 Bank Panel with Priority Fill Selection	70 x 40 x 21	(1778 x 1016 x 533)	1058	480
AC70530T-4D	Stationary, 4 Bank Panel with Remote Fill & Priority Fill Selection	70 x 40 x 21	(1778 x 1016 x 533)	1061	481
AC70530TB	Stationary, Bulk Fill Panel	70 x 40 x 21	(1778 x 1016 x 533)	1045	474

\*Adaptors for filling SCUBA cylinders may be purchased seperately.

PO Box 1000 | Sophia, WV 25921-1000  
 304-683-4595 | 304-683-3257 | 800-523-7222  
 sales@americanairworks.com | www.americanairworks.com

